




RECESSED ELECTRIC FIREPLACE



Owner's Manual

Model Number	Item Number
EF-136P	EF10141



READ & SAVE THESE INSTRUCTIONS

Carefully read and review before assembling, installing, operating, or maintaining this product. Observe all safety instructions and information.

FAILURE TO FOLLOW WARNINGS & OPERATIONAL INSTRUCTIONS CONTAINED IN THIS MANUAL CAN RESULT IN PROPERTY DAMAGE OR PERSONAL INJURY

IMPORTANT NOTICE

For customer service & warranty issues, please contact: **customercare@jrhome.com**Electric fireplace inserts and free standing electric fireplaces heaters rated at 1500w/ 5000 BTU

Introduction




THIS APPLIANCE IS HOT WHEN OPERATED AND CAN CAUSE SEVERE BURNS IF CONTACTED.

- Do not operate appliance before reading and understanding operating instructions. Failure to operate appliance according to operating instructions could cause fire or injury.
- Risk of burns. Power to the appliance should be turned off and the appliance allowed to cool before servicing. To disconnect power to the appliance, turn controls to off, then remove plug from outlet.
- Do not install damaged, incomplete or substitute components.
- Do not burn wood or other materials in this appliance.
- Young children should be carefully supervised when they are in the same room as the appliance. Toddlers, young
 children and others may be susceptible to accidental contact burns. A physical barrier is recommended if there are
 at risk individuals in the house. To restrict access to an appliance or stove, install an adjustable safety gate to keep
 toddlers, young children and other at risk individuals out of the room and away from hot surfaces.
- Clothing or other flammable material should not be placed on or near the appliance.
- Due to high temperatures, the appliance should be located out of traffic and away from furniture and draperies.
- Ensure you have incorporated adequate safety measure to protect infants/toddlers from touching hot surfaces.
- Even after the appliance is out, the glass and/or screen will remain hot for an extended period of time.
- Check with your local hearth specialty dealer for safety screens and hearth guards to protect children from hot surfaces. These screens and guards must be fastened to the floor.
- Any safety screen or guard removed for servicing must be replaced prior to operating the appliance.
- It is imperative that the control compartments, circulating blower and its passageway in the appliance and are kept clean. The appliance should be inspected before use and at least annually by a qualified service person. More frequent cleaning may be required due to excessive lint from carpeting, bedding material, etc. The appliance area must be kept clear and free from combustible materials, gasoline and other flammable vapors and liquids.
- Under no circumstances should this appliance be modified.
- Do not use this appliance if any part has been under water. Immediately call a qualified service technician to inspect the appliance and to replace any part of the control system which has been under water.
- Do not operate the appliance with the glass door removed, cracked or broken. Replacement of the glass should be done by a licensed or qualified service person.
- Do not strike or slam shut the appliance glass door.
- Keep the packaging material out of reach of children and dispose of the material in a safe manner. As with all plastic bags, these are not toys and should be kept away from children and infants.
- Servicing should be done only while the appliance is disconnected from the power supply circuit.
- Always unplug appliance when not in use.
- Do not operate this appliance with a damaged cord or plug after the appliance malfunctions, has been dropped or damaged in any manner. Return appliance to authorized service facility for examination, electrical or mechanical adjustment, or repair.
- Do not use outdoors.
- Never locate appliance where it may fall into a bathtub or other water container.
- Do not run cord under carpeting. Do not cover cord with throw rugs, runners, or the like. Arrange cord away from traffic area and where it will not be tripped over.
- Connect to properly grounded outlets only.
- Do not insert or allow foreign objects to enter any ventilation or exhaust opening as this may cause an electric shock or fire, or damage the appliance.
- To prevent a possible fire, do not block air intakes or exhaust in any manner. Do not use on soft surfaces, like a carpet, where openings may become blocked.
- Always plug appliances directly into a wall outlet/receptacle. Never use an extension cord, relocatable power tap (outlet/power strip) or adapter.
- Ensure clearances to combustibles are maintained when building a mantel or shelves above the appliance.
 Elevated temperatures on the wall or in the air above the appliance can cause melting, discolouration or damage to decorations, a T.V. or other electronic components.

Page 2 06.12.23

Dimensions



This appliance has been tested in accordance with the CSA Standards for fixed and location-dedicated electric room appliances in the United States and Canada. If you need assistance during installation, please contact your local dealer.

NOTE: This appliance must be electrically wired and grounded in accordance with local codes or, in the absence of local codes, with National Electric Code ANSI/NFPA 70-latest edition in the United States or the Canadian Electric Code, CSA C22.1 in Canada.

Technical Specification

Description of product	ELECTRIC FIREPLACE
Model	EF-136P
Rated Voltage	120V~
Rated Frequency	60 Hz
Rated Power	1500W
Lamp	LED

General Instructions

WARNING

READ THESE INSTRUCTIONS COMPLETELY BEFORE BEGINNING INSTALLATION. FAILURE TO FOLLOW THEM COULD CAUSE AN APPLIANCE MALFUNCTION RESULTING IN SERIOUS INJURY AND/OR PROPERTY DAMAGE.

ALL ELECTRIC APPLIANCES HAVE HOT AND ARCING OR SPARKING PARTS INSIDE. DO NOT USE IT IN AREAS WHERE GASOLINE, PAINT OR FLAMMABLE LIQUIDS ARE PRESENT.

THIS ELECTRIC APPLIANCE IS TESTED AND LISTED FOR USE ONLY WITH THE OPTIONAL ACCESSORIES LISTED IN THESE INSTRUCTIONS. USE OF OPTIONAL ACCESSORIES NOT SPECIFICALLY TESTED FOR THIS ELECTRIC APPLIANCE COULD VOID THE WARRANTY AND/OR RESULT IN A SAFETY HAZARD.

DO NOT OPEN. RISK OF ELECTRIC SHOCK. NO USER-SERVICEABLE PARTS INSIDE.

DO NOT USE DAMAGED ELECTRICAL CORDS.

SERVICING SHOULD BE DONE ONLY WHILE THE APPLIANCE IS DISCONNECTED FROM THE POWER SUPPLY CIRCUIT.

TO PREVENT ELECTRIC SHOCK MATCH THE WIDE BLADE OF PLUG TO WIDE SLOT OF RECEPTACLE AND FULLY INSERT.

- 1. Prior to plugging your appliance into an electrical outlet, verify that the house circuit breakers for the outlet are on.
- 2. The appliance may emit a slight, harmless odour when first used. This odour is normal and it is caused by the initial heating of internal appliance elements and will not occur again.
- 3. If your appliance does not emit heat, consult the operation section of this manual for further information.
- 4. Use with a CSA or UL certified surge protector.
- 5. Do not route the power cord directly underneath the appliance.

This electric appliance meets the construction and safety standards of H.U.D. for application in manufactured homes when installed according to these instructions.


As with most electronic devices, your new electric fireplace has been designed to operate at temperatures between 5°C (41°F) and 35° C (95°F). During the colder winter months, allow the fireplace to reach room temperature before turning it on.

Unpacking and Testing Appliance

Carefully remove the appliance from the box. Prior to installing the appliance, test to make sure the appliance operates properly by plugging the power supply cord into a conveniently located 120 Volt grounded outlet.

Page 4 06.12.23

Hardware Parts List



Locating Appliance

WARNING

DUE TO HIGH TEMPERATURES, THIS ELECTRIC APPLIANCE SHOULD BE LOCATED OUT OF TRAFFIC. KEEP COMBUSTIBLE MATERIALS SUCH AS FURNITURE, PILLOWS, BEDDING, PAPERS, CLOTHES AND CURTAINS AT LEAST 36" (914mm) FROM THE FRONT OF THE APPLIANCE.

NEVER LOCATE THIS ELECTRIC APPLIANCE WHERE IT MAY FALL INTO A BATHTUB OR OTHER WATER CONTAINER.

WEAR SAFETY GLOVES AND SAFETY GLASSES FOR PROTECTION DURING INSTALLATION AND MAINTENANCE.

TO PREVENT CONTACT WITH SAGGING OR LOOSE INSULATION, THE ELECTRIC APPLIANCE MUST NOT BE INSTALLED AGAINST VAPOR BARRIER OR EXPOSED INSULATION. LOCALIZED OVERHEATING COULD OCCUR AND A FIRE COULD RESULT.


DO NOT EXPOSE THE ELECTRIC APPLIANCE TO THE ELEMENTS (SUCH AS RAIN, ETC.)

Grounding Appliance

This appliance is for use on 120 Volts. The cord has a plug as shown in (A).

To disconnect appliance, turn controls to off, then remove plug from outlet.

GROUNDING METHODS



Page 6 06.12.23

Installation

WARNING

RISK OF FIRE! THE POWER CORD MUST NOT BE PINCHED AGAINST A SHARP EDGE. SECURE CORD TO AVOID TRIPPING OR SNAGGING TO REDUCE THE RISK OF FIRE, ELECTRIC SHOCK OR PERSONAL INJURY. DO NOT RUN CORD UNDER CARPETING. DO NOT COVER CORD WITH THROW RUGS, RUNNERS OR THE LIKE. ARRANGE CORD AWAY FROM TRAFFIC AREAS AND WHERE IT WILL NOT BE TRIPPED OVER.

RISK OF FIRE! TO PREVENT A POSSIBLE FIRE, DO NOT BLOCK AIR INTAKE OR EXHAUST IN ANY MANNER. DO NOT USE ON SOFT SURFACES WHERE OPENINGS MAY BECOME BLOCKED.

RISK OF FIRE! DO NOT BLOW OR PLACE INSULATION AGAINST THE APPLIANCE.

THIS ELECTRIC APPLIANCE IS TESTED AND LISTED FOR USE ONLY WITH THE APPROVED OPTIONAL ACCESSORIES. USE OF OPTIONAL ACCESSORIES NOT SPECIFICALLY TESTED FOR THIS ELECTRIC APPLIANCE COULD VOID THE WARRANTY AND/OR RESULT IN A SAFETY HAZARD.

IF THE INFORMATION IN THESE INSTRUCTIONS IS NOT FOLLOWED EXACTLY, A FIRE OR EXPLOSION MAY RESULT CAUSING PROPERTY DAMAGE, PERSONAL INJURY OR DEATH. DO NOT STORE OR USE GASOLINE OR OTHER FLAMMABLE VAPORS IN THE VICINITY OF THIS OR ANY OTHER APPLIANCE.

THIS APPLIANCE IS HEAVY. IT IS HIGHLY RECOMMENDED THAT TWO PEOPLE INSTALL THIS APPLIANCE.

HEATER VENTS ON THE ELECTRIC APPLIANCE CANNOT, IN ANY WAY, BE COVERED AS IT MAY CREATE A FIRE HAZARD.

DO NOT RUN THE POWER CORD HORIZONTALLY, DIRECTLY BELOW THE APPLIANCE.

Your EF-136P unit is an insert. Select a suitable location that is not susceptible to moisture and is away from drapes, furniture and high traffic areas.

NOTE: Follow all National and local electrical codes.

Minimum Clearance to Combustibles

Measurements are taken from the glass front				
Bottom	0"	Тор	8" (203mm) to mantel	
Sides	0"	Тор	8" (203mm) to ceiling	
Back	0"			

Minimum Mantel Clearances




WHEN USING PAINT OR LACQUER TO FINISH THE MANTEL, THE PAINT OR LACQUER MUST BE HEAT RESISTANT TO PREVENT DISCOLOURATION.

Installation

Recessing the Appliance Flush into the Wall

Due to the many different finish materials used on walls, it is highly recommended that you consult your local builder before you install this appliance in the wall.



Page 8 06.12.23

Finishing

WARNING

POWER SUPPLY SERVICE MUST BE COMPLETED PRIOR TO FINISHING TO AVOID RECONSTRUCTION.


HEAT VENTS AND AIR OPENINGS CANNOT BE COVERED IN ANY CIRCUMSTANCES.

Front Glass Removal / Installation



BEFORE THE FRONT GLASS IS INSTALLED OR REMOVED, UNPLUG THE APPLIANCE AND WAIT UNTIL APPLIANCE IS COOL TO THE TOUCH, GLASS CAN BE HEAVY AND FRAGILE SO HANDLE WITH CARE.


- 1. Remove the 4 screws from the sides of the appliance in Figure 1.
- 2. Have two people lift the glass up and away from the appliance, holding the glass vertical while carrying. Carefully rest the glass on a soft, non-abrasive surface.
- 3. Re-install the front glass by aligning the slots with the pins on the side of the appliance. Press the glass down to secure in place.
- 4. Secure the front glass using the 4 screws in Figure 1. (If fully recessed, this is not necessary)




Trim Installation

⚠ WARNING

BEFORE THE FRONT GLASS IS INSTALLED OR REMOVED, UNPLUG THE APPLIANCE AND WAIT UNTIL APPLIANCE IS COOL TO THE TOUCH. GLASS CAN BE HEAVY AND FRAGILE SO HANDLE WITH CARE.



STEP 2



Page 10 06.12.23

Operating Instructions

MARNING

WHILE THE APPLIANCE IS OPERATING DO NOT REMOVE THE GLASS PANEL. THIS WILL CAUSE THE REMOTE CONTROL TO FUNCTION IMPROPERLY.

Once the appliance has been plugged into a grounded electrical outlet, it is ready to operate.

NOTE: Ensure the house circuit breakers for the power supply are turned on. In the event of a powerfailure, the appliance will lose its memory function and will reset to factory mode when the power returns.


Main Power Switch

To turn unit power on:

- 1. Plug in power cord. If hard wired, just turn on the power switch on the unit.
- 2. Verify the power is turned on when two ring tones are initiated.

Operating with Button

Heater Indicator




FUNCTION	ICON	DISPLAY		OPERATION DETAILS
Flame	The LED flame	N/A		Turn on the flame total 7 levels with high brightness Level.(Red,Yellow,Blue,Red yellow,Red blue,Yellow blue,Red yellow blue)
Heater	(%)	SSS	First press	Turns on 2 heating system elements at Highest Level 1500W. Indicator shows red.
	Press button to adjust	\$\$\$	Second press	Turns on 1 heating system element at Lowest Level 750W. Indicator shows blue.
	heater and blower	· \$\$\$	Third press	Turns off heating system and blower
Timer		• (L)		Heater timer is set


The onboard buttons are located under the trim on the top right

FUNCTION	ICON	DI	SPLAY	OPERATION DETAILS
Power	Ф	ON	First click	Turn on the yellow flame at the brightest level.Ember bed color is red. Top light color is white. Heater is off.
		OF	Second click	Turn off the fireplace main power
Flame	((())))	ON	First click	Turns on flame colour, ember bed LEDs and top light.
		OF	Second click	Turns off flame, ember bed LEDs and top light.
Note: Third click, I	LED setting will I	esume t	o previous set	ting
Temperature	°C / °F Click to toggle	8	1 B°c	Celsius degree
	between Celsius and Fahrenheit.	8	8.₅	Fahrenheit degree
Note: Room tempe	erature will displa	ay the cu	ırrent room ter	nperature in Celsius or Fahrenheit degree
		16	88°°	16 Celsius degrees
Temperature	\triangle	19	89°c	19 Celsius degrees
		21	28°C	21 Celsius degrees
	Adjust heater and	23	23°c	23 Celsius degrees
	display temperature	25	25°C	25 Celsius degrees
		27	88°c	27 Celsius degrees
		30	38°c	30 Celsius degrees
		61	88. _F	61 Fahrenheit degrees
		66	88 ⋅ ,	66 Fahrenheit degrees
		70	88	70 Fahrenheit degrees
		73	88∘ғ	73 Fahrenheit degrees
		77	<i>88</i> ⋅ F	77 Fahrenheit degrees
		80	88 ⋅ ₽	80 Fahrenheit degrees
		86	88. • ₽	86 Fahrenheit degree



Page 12 06.12.23







FUNCTION	ICON	DI	SPLAY	OPERATION DETAILS	
Top Light	-D-	C1	8.8.	Red	
	,	C2	8.8	Orange	
		C3	88	Yellow	
		C4	88	Forest green	
		C5	8.5	Green	
		C6	88	Blue	
		C7	8.8.	Sea blue	
		C8	8.8	Cyan	
		C9	88	White	
		CA	88	Purple	
		Cb	88	Pink	
		СС	8.8.	Color- rotating	
		CL	88	Rainbow	
Note: After 'CL', pr	ess one more ti	me top li	ght will turn of	f	
Ember Bed	-``	E1	8.8	Red	
		E2	8.8	Orange	
		E3	88	Yellow	
		E4	88	Forest green	
		E5	8.5.	Green	
		E6	88	Blue	
		E7	8.8	Sea blue	
		E8	88	Cyan	
		E9	8.8	White	
		EA	88	Purple	
		Eb	88	Pink	
		EC	8.8.	Color- rotating	
		EL	88	Rainbow	
Note: After 'EL',	Note: After 'EL', press one more time ember bed light will turn off				



Page 14 06.12.23

FUNCTION	ICON	DISPLAY	OPERATION DETAILS
Heater	(short press)	First click	Turn on two group the heating system at 1500W high level
		†† Second click	Turn on one group the heating system at 750W low level
Note: Third click, T	urn off all heatin	g system and blower	
Timer	Č	<i>30</i> min	30 minutes
		[] hrs	1 hour
		2 hrs	2 hours
		3 hrs	3 hours
		4 hrs	4 hours
		5 hrs	5 hours
		5 hrs	6 hours
		hrs	7 hours
		8 hrs	8 hours
		9 hrs	9 hours
		N/A	OFF
Favourite flame lights settings	(Press and hold for 3 seconds)	•	Save 1 setting of the flame LEDs as a favourite

Note: If you want to return to preset stage, press the key for 3 seconds. It only memorizes one storage of flame setting, the new setting will override the previous setting.

Remote Control Specification

1.Model: R220 2.Remote Key: 13

3.Communication: Infrared 4.Infrared Distance: 6 Meters

5.Battery: AAAx 2pcs

NOTE: Make sure your "AAA" batteries (x2) are fully charged and installed correctly in your remote control before operating.

The remote control must remain within 6 meters of the appliance to be effective, this range may be reduced when battery power is depleted.



Maintenence



PREPARATION FOR MAINTENANCE

ALWAYS DISCONNECT THE POWER AND ALLOW THE ELECTRIC APPLIANCE TO COOL BEFORE PERFORMING ANY CLEANING, MAINTENANCE OR RELOCATION OF THIS ELECTRIC APPLIANCE. TURN CONTROLS TO OFF AND REMOVE PLUG FROM OUTLET OR TURN OFF THE HOUSE CIRCUIT BREAKER TO ELECTRIC APPLIANCE RECEPTACLE.

DO NOT INSTALL LED LIGHT STRIPS THAT EXCEED SPECIFIED MAXIMUM WATTS.

THE LED LIGHT STRIPS IN YOUR APPLIANCE CAN BECOME EXTREMELY HOT. ALLOW AT LEAST 10 MINUTES BETWEEN TURNING OFF THE APPLIANCE AND REMOVING THE STRIPS TO AVOID ACCIDENTAL BURNS.

DO NOT HANDLE THE LED LIGHT STRIPS WITH BARE FINGERS. USE GLOVES OR A CLEAN DRY CLOTH WHEN HANDLING.

Storage Instructions

Ensure the power cord is not installed so that it is pinched or against a sharp edge and ensure that the power cord is stored or secured to avoid tripping or snagging to reduce the risk of fire, electric shock, or injury to persons.

Construction and electrical outlet wiring must comply with local building codes and other applicable regulations to reduce the risk of fire, electrical shock, and injury to persons.


Do not attempt to wire your own new outlets or circuits. To reduce the risk of fire, electric shock, or injury to persons, always use a licensed electrician.

Page 16 06.12.23

Wiring Diagram

WARNING

TURN OFF THE APPLIANCE COMPLETELY AND LET COOL BEFORE SERVICING. ONLY A QUALIFIED SERVICE PERSON SHOULD SERVICE AND REPAIR THIS ELECTRIC APPLIANCE.



Hard Wiring Installation



TURN OFF THE APPLIANCE COMPLETELY AND LET COOL BEFORE SERVICING. ONLY A QUALIFIED SERVICE PERSON SHOULD SERVICE AND REPAIR THIS ELECTRIC APPLIANCE.

HARD WIRING CONNECTION

If it is necessary to hard wire this appliance, a qualified electrician must remove the cord connection, and wire the appliance directly to the house hold wiring.

This appliance must be electrically connected and grounded in accordance with local codes, if hard wired. In the absence of local codes, use the current CSA C22.1 CANADIAN ELECTRICAL CODE in Canada or the current ANSI/NFPA 70 NATIONAL ELECTRICAL CODE in the United States.

COVER PLATE






Figure 1

- 1. Remove the cover plate from the right side of the appliance by removing the four screws, as shown above.
- 2. Remove the wire connectors from the power cord. The power cord may be discarded.
- 3. Using the wire connectors, connect the ground green wires (G) and white wires (N) together, then hot black wires (L) and then refer to Figure 2.
- 4. Reinstall the cover plate using the four screws, as shown in Figure 1.

NOTE: Leave enough wire so that the appliance can be removed from the enclosure without disconnecting the power supply.

Figure 2



Replacement Parts



FAILURE TO POSITION THE PARTS IN ACCORDANCE WITH THIS MANUAL OR FAILURE TO USE ONLY PARTS SPECIFICALLY APPROVED WITH THIS APPLIANCE MAY RESULT IN PROPERTY DAMAGE OR PERSONAL INJURY.

To order parts, contact customercare@jrhome.com

FOR WARRANTY REPLACEMENT PARTS, A PHOTOCOPY OF THE ORIGINAL INVOICE WILL BE REQUIRED TO HONOUR THE CLAIM.

When ordering replacement parts always give the following information: • Model and serial number of appliance

- Installation date of appliance
- Part number
- Description of part
- Finish

FOR FURTHER INFORMATION, CONTACT CUSTOMERCARE@JRHOME.COM or call 1-800-561-5550.

COMPONENTS			
REF.	LUX36	DESCRIPTION	
1	36FG	Front Glass	
2	36BBLL	Ember Bed LED Light	
3	36FLL	Flame LED light	
4	36RBH	Reflective brush combination	
5	36ВНА	Blower and Heater Assembly	
6	36CB	Circuit Board	
7	36RC	Remote Control	
8	36RCR	Remote Control Receiver	
9	36FM	Flame motor 120V/10/12RPM	
10	36RML	Ribbon of magic lights circuit board	


MARNING

This product can expose you to chemicals including Carbon Black, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www. P65Warnings.ca.gov

Replacement Parts Diagram

WARNING

FAILURE TO POSITION THE PARTS IN ACCORDANCE WITH THIS MANUAL OR FAILURE TO USE ONLY PARTS SPECIFICALLY APPROVED WITH THIS APPLIANCE MAY RESULT IN PROPERTY DAMAGE OR PERSONAL INJURY.



NOTE: Care must be taken when removing and disposing of any broken glass or damaged components. Be sure to vacuum up any broken glass from inside the appliance before operation.

Page 20 06.12.23

Troubleshooting

/!\ WARNING

TURN OFF THE APPLIANCE COMPLETELY AND LET COOL BEFORE SERVICING. ONLY A QUALIFIED SERVICE PERSON SHOULD SERVICE AND REPAIR THIS ELECTRIC APPLIANCE.

Symptom	Problem	Test Solution
Dim or no flame/ Ember bed is not glowing or dimming	LED's are burnt out or malfunctioning	Inspect the LED's and replace them if necessary
No warm air coming out of appliance	Room temperature is higher than the appliance setting (if it is set to room temperature)	Reset temperature setting
	Heater is burnt out	Inspect the burner and heater assembly and replace it if necessary
Appliance turns off and will not turn on	Electric firepalce has overheated and safey device has caused thermal switch to disconnect or home circuit breaker has opened.	Reset switch by turing main power switch off and waiting 5 minutes then turning it back on.
Remote control does not work	Low battery	Replace battteries in remote control
Heater shuts off automatically	Room is too warm	The heater has a built-in thermostat so it will shut off automatically once the pre-set temperature is reached. It will also turn on automatically if the room temperature drops below the pre-set temperature.

Review & Warranty Extension









patioflare elements



Extend Your Warranty By Leaving A Review

We want your opinion about your purchase...and we want you to tell everyone about it! Just leave a review for the product on the retailers website where you made your purchase, or at www.jrhome.com, and fill in the online warranty at https://www.jrhome.com/warranty-registration to receive a complimentary extra year of warranty protection.

Follow us on:











www.jrhome.com

#ActiveFlame #jrhome

IMPORTANT



For questions, concerns or problems with our product please email our customer service department:

customercare@jrhome.com

DATED PROOF OF PURCHASE REQUIRED FOR WARRANTY SERVICE

WARRANTY

This product is inspected, tested and carefully packaged to minimize the chance of damage during shipment. If a part (excluding light bulbs, glass and fuses*) within two years from the date of purchase proves to be defective in material or fabrication under normal use, the part will be repaired or replaced. The Company's obligation under the warranty is to replace or repair defective parts at our discretion. Any expenses or damage resulting from the installation, removal or transportation of the product will be the responsibility of the owner and are not covered by this warranty. The owner assumes all other risks arising from the use or misuse of the product. The warranty will be void if the product damage or failure is deemed by the Company to be caused by accident, alteration, misuse, abuse, incorrect installation or removal, or connection to an incorrect power source by the owner. The Company neither assumes, nor authorizes any person or entity to assume for it any obligation or liability associated with its products. Light bulbs and fuses are not covered under this warranty. If you have any questions regarding the warranty or service, please contact us at customercare@jrhome.com.

Customer Service: JR Home Products

Unit 306 - 19100 Airport Way, Pitt Meadows, BC V3Y 0E2

Toll Free: 1-800-561-5550

E-mail: customercare@jrhome.com

You MUST register your product within 30 days of purchase to receive warranty service.

Registration can be completed online at www.jrhome.com or by mailing this form.

Si vous éprouvez des difficultés ou si vous avez des questions ou des préoccupations, prière de faire parvenir un courriel à notre service à la clientèle customercare@jrhome.com

UNE PREUVE D'ACHAT DATÉE EST REOUISE POUR SE PRÉVALOIR DE LA GARANTIE.

AVERTISSEMENT

Ce produit a été soigneusement inspecté, testé et emballé afin de minimiser les risques de dommages durant le transport. Si l'une des pièces (à l'exception des verres, des ampoules électriques et des fusibles*) s'avère défectueuse au niveau de sa fabrication ou de ses matériaux dans les deux ans qui suit la date de l'achat suite à une utilisation normale, la pièce sera réparée ou remplacée. La compagnie est tenue de réparer ou remplacer les pièces défectueuses à sa discrétion, en vertu de la garantie. Tous frais ou dommage résultant de l'installation, du démantèlement ou du transport du produit demeurent la responsabilité du client et n'est pas couvert par cette garantie. Le client assume tout autre risque résultant de l'utilisation correcte ou fautive du produit. La garantie devient nulle si la compagnie détermine que le dommage ou le mauvais fonctionnement est causé par un accident, une modification, une mauvaise utilisation, un abus, une mauvaise installation ou un mauvais démantèlement ou un branchement à une source électrique inadéquate de la part du client. La compagnie n'est pas responsable et n'autorise quiconque, personne ou entité légale, à accepter de responsabilité ou obligation en son nom, en rapport avec ses produits. * Les ampoules électriques et les fusibles ne sont pas couverts par cette garantie. Pour toute question au sujet de la garantie ou du service, contacter le service à la clientèle à : customercare@jrhome.com.

Service à la clientèle:

JR Home Products

Unit 306 - 19100 Airport Way, Pitt Meadows BC V3Y 0E2 Numéro

sans frais: 1-800-561-5550

Courriel: customercare@jrhome.com

Vous DEVEZ enregistrer votre produit dans les 30 jours suivant l'achat pour bénéficier du service degarantie. L'enregistrement sera complet une fois que vous aurez posté ce formulaire ou que vous serez inscrit en ligne.

Warranty Registration Information Form / Formulaire d'enregistrement de la garantie

Name / Nom :	
Street / Adresse :	You MUST regis warranty service.
City / Ville :	,
Province / Province :	For warranty se
Postal Code / Code postal :	
Daytime Phone # / No téléphone jour :	coordinated by J&R Home Produc
Evening Phone # / No téléphone soir :	Vous DEVEZ enre prévaloir de la gar
E-Mail Address / Courriel :	Afin de faire valo avec J&R Home numéros indiqués
Product/Produit :	suivant la date d'a
Place of Purchase / Lieu de l'achat :	aux garanties ser
Date of Purchase / Date de l'achat :	service de J&R H
Model # / No de modèle :	
Serial # / Numéro de série :	

ster your product to receive

ervice, contact J&R Home ddress, phone numbers listed days of purchase. Be sure to receipt and original date of warranty service will be

cts service center

egistrer votre produit pour vous

ir la garantie, communiquez Products à l'adresse et aux ci-dessous dans les 30 iours achat. Ayez en main votre reçu Toutes les demandes liées ront traitées par le centre de ome Products.